

Pressure Gauges / Accurate Pressure Gauges / Standard Types / Ø 160 mm.

CONSTRUCTIVE PROPERTIES

	STANDARD	OPTIONAL
Mounting Type	Bottom Connection	See Technical Drawing
Scale Unit	bar/psi	bar psi kg/cm ²
Scale Range (PN)	0/0,6 0/1 0/1,6 0/2,5 0/4 0/6 0/10 0/16 0/25 0/40 0/60 0/100 0/160 0/250 0 - 315 0/400 0/600	
Vacuum Scale Range	-1 / 0 -1 / +0,6 -1 / +1,5 -1 / +3 -1 / +5 -1 / +9 -1 / +15 -1 / +24	
Case	Steel (Black Enamelled)	-
Bezel	Black Enamel (Bajonet)	-
Window	-	-
Movement	Brass	-
Wetted Parts	Copper Alloy	-
Connection	G 1/2" B	1/2" NPT
Dial	Aluminum	-
Pointer	Aluminum	Adjustable Aluminum
Welding	Soldering	Hard Soldering


**MH160DRM1**

Bottom Connection

USAGE PROPERTIES


Fluid Temperature	Maximum + 60 °C	Maximum + 120 °C
Ambient Temperature	- 20 ... + 60 °C	-
Operating Pressure (max.)	Must not exceed full scale.	
Over Pressure Limit	F.S. x 1,3	-
Accuracy Class	CL 1.0	-
Protection Rate	IP 41	-
Optimum Operating Range	Between 0,0 x PN and 1,0 x PN	
Storage Temperature	-40 ... +70 °C	-
Conformity	EN 837 - 1	-
Mechanical Shock Test Load	15g	-
Mechanical Vibration Test	10 Hz ile 150 Hz -1 oktav/dk. 2s / 3 eksende	

Pressure Gauges / Accurate Pressure Gauges / Standard Types / Ø 160 mm.




Model No: MH160DRM1

Bottom Connection




Model No: MH160DRM4

Lower Back Connection




Model No: MH160DRM5

Lower Back Panel Mount Connection



Model No: MH160DRM6

Bottom Connection with Back Flange



Model No: MH160DRM8

Lower Back Connection with Front Flange